

CHECK VALVES



Series CKM

Patented design closes automatically, requires no reverse pressure 1/2", 3/4", 1" PVC, CPVC, GPP, PVDF, PTFE



Series CKS

Isolated spring closes valve automatically, requires no reverse pressure 1 1/2", 2", 3", 4" PVC, CPVC, PP, PVDF



Series CKD

Specialty diaphragm design opens with virtually no forward pressure 1/4", 1/2" PVC, PP, PVDF, PTFE

VACUUM BREAKERS



Series VBM

Patented design closes automatically, requires no reverse pressure 1/2", 3/4", 1" PVC, CPVC, GPP, PVDF, PTFE



Series VBS

Isolated spring closes valve automatically, requires no reverse pressure 1-1/2", 2", 3", 4" PVC, CPVC, PP, PVDF

RELIEF, BY-PASS & BACKPRESSURE VALVES



Series RVDT/RVDTM

PTFE diaphragm design has no wetted elastomers; 1st State-approved thermoplastic anti-siphon valve; superior performance and cycle life. Inline flow pattern 1/4", 1/2", 3/4", 1", 1 1/2", 2", 3" PVC, CPVC, PP, PVDF, PTFE, SS



Series TRVDT

3-port valve, PTFE diaphragm design has no wetted elastomers; simplifies piping 1/2", 3/4", 1" PVC, CPVC, PP, PVDF, PTFE,



Series RVT/RVTX

Angle flow pattern with PTFE shaft. High flow rates in a design proven for over 50 years 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3" PVC, CPVC, PP, PVDF, PTFE



Series RVD

Angle flow pattern with PTFE spring guides. Compact, rugged design 1/4", 1/2" PVC, CPVC, PP, PVDF, PTFE



Series RVDM

Inline pattern with ultra smooth flow performance, light weight 1/2", 3/4", 1" PVC, CPVC, GPP, PVDF

HIGH PERFORMANCE PRESSURE REGULATORS



Series PRH/PRHM

Rolling diaphragm, extended shaft and multiple spring design is the industry standard for thermoplastic pressure regulators. Set pressure range from 5 to 125 PSI on most models. 1/4", 1/2", 3/4", 1", 1 1/2", 2", 3", 4" PVC, CPVC, PP, PVDF, PTFE



Series PRA

Air-piloted design provides superior flow with industry's lowest drop-off from set pressure (droop). Set pressure range from 5 to 125 PSI. 1/4", 1/2", 3/4", 1", 1 1/2", 2", 3" PVC, PP, PVDF



Series PRS

Optional patented Stabilizer is used with Series PRA. The Stabilizer reacts to downstream liquid pressure and provides continuous feedback control to the compressed air supply, for the ultimate regulator sensitivity and performance. PVC, PP, PVDF, PTFE



Series PRD/PRDM

Differential pressure regulator eliminates overpressure across a bank of filters, etc. via tubing connected downstream. Set range to 50 PSI. 1/4", 1/2", 3/4", 1", 1 1/2", 2", 3" PVC, PP

ULTRA PURE PRESSURE REGULATORS



Series PRHU

Kynar machined body with metal ion-free EPDM rolling diaphragm, IPS or metric spigot connections. Highest flow performance in ultra-pure valve with 10 to 125 PSI set range. 1/2" - 3" or 20 mm - 90 mm Kynar 740 PVDF



Series UPR

Kynar machined body with no wetted elastomers; variable area PTFE diaphragm provides excellent pressure response. UPR is a non-shutoff design with 5 to 100 PSI set range. 1/4" NPT or Flare; PVDF or PTFE 20, 25, 32, 50, 63mm spigot; PVDF

PROCESS COOLING WATER STICK



Series PCWS

Supply side stick strengthens piping and reduces installation costs. Configurations include options with or without ball valve, diaphragm valve, y-strainer, pressure regulator, pressure gauge, Tridicator, and a variety of connection types. 1/2", 3/4", 1", 1 1/2", 2" PVC, CPVC



Series PCWR

Return stick strengthens piping and reduces installation costs. Configurations include options with or without ball valve, diaphragm valve, flow meter, pressure gauge, Tridicator, and a variety of connection types. 1/2", 3/4", 1", 1 1/2", 2" PVC, CPVC

SOLENOID VALVES



Series EASYMT/EASMT

Normally-closed design/energize to open. Million-cycle design featuring PTFE bellows; direct acting. Available with choice of rectified coil or rectified "Z-Cool"

energy saving 24 watt coil. 120/60, 24/60, 240/60 AC or 24V DC 1/4", 1/2", 3/4", 1" sizes with 3/8"-1 1/16" main orifice
PVC, CPVC, GPP, PVDF



Series EAST

Compact, normally-closed design/energize to open. Million-cycle design featuring PTFE bellows; direct acting. Available with 11 watt, NEMA 4X coil.

120/60, 24/60, 240/60, 230/50 AC or 24V DC 1/4", 1/2" sizes with 3/16" or 1/4" main orifice
PVC, PP, PVDF



PS

Pilot-operated, normally-closed design/energize to open. Million-cycle high flow rate valve features PTFE bellows; require pressure differential to function. Available with 11 watt, NEMA 4X coil.

120/60, 24/60, 240/60, 230/50 AC or 24V DC 1/4", 1/2", 3/4", 1", 1 1/2", 2", 3"
PVC, CPVC, PP, PVDF

SPECIAL-PURPOSE SOLENOID VALVES



Series EASY

Normally-open design/energize to close for process requiring continuous flow with occasional shutoff. Available with choice of rectified coil or rectified "Z-Cool"

energy saving 24 watt coil. 120/60, 24/60, 240/60 AC or 24V DC 1/4", 1/2" sizes with 1/4" main orifice
PVC



Series THP

3-way valve, also known as a diverter valve. Direct acting. Available with choice of rectified coil or rectified "Z-Cool" energy saving 24 watt coil.

120/60, 24/60, 240/60 AC or 24V DC 1/4", 1/2" sizes with 1/8", 3/16" or 1/4" main orifice
PVC

AIR RELEASE & DEGASSING VALVES



Series ARV

Provides rapid expulsion of air at start-up; seals bubble-tight while system operates. Dust cap optional.

1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"
PVC, CPVC, PP, PVDF



Series DGV

Provides continuous venting of trace amounts of air/gas as it occurs during system operations.

1/2"
PVC, CPVC, PP, PVDF, Clear Acrylic



Series CARD

Combines ARV initial volume venting & DGV continuous trace venting in one unit.

1", 2", 4"
PVC, CPVC

PULSATION DAMPENER/SUPPRESSOR



Series PDS

Performs six functions to improve system performance: Pulsation Dampener smooths pump flow, Surge Suppressor absorbs vibrations, Water Hammer

Arrestor, Inlet Stabilizer enhances pump operation, Accumulator releases stored fluid during unwanted pressure drops, Expansion Tank protects system from thermal volume increases. 10, 50 and 180 cubic inch capacity in 1", 2", 3" connection, respectively.
PVC, CPVC, PP, PVDF

SHUTOFF VALVES



Series BSDA/BSDAM

Air operated, compact PTFE diaphragm valve for drain applications and pressures to 100 PSI.

1/4", 1/2", 3/4", 1", 1 1/2"
PVC, CPVC, PP, PVDF, PTFE

Series BSR/BSRM

Air operated, balanced shaft design assures bubble tight shutoff with automatic spring return.

1/2", 3/4", 1", 1 1/2", 2"
PVC, PP



Series MFR

Hand or foot operated manual valve. Press to open, automatic spring return closure.

1/2", 3/4"
PVC



Series HSA

Air operated pinch valve ideal for slurries or particulate. EPDM sleeve closes bubble-tight around media.

1/2", 3/4", 1"
PVC, CPVC, PP, PVDF

FLOW CONTROL VALVES



Series FC

Internal snubber and orifice plate maintains constant, pre-set flow despite pressure fluctuations. Flow rate is tamper-proof and available from 1/4 GPM to 120 GPM.

1/4", 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3"
PVC

GAUGE GUARDS & INSTRUMENTATION



Series GGS

Heavy duty instrument isolator; 1/2" process connection with steel reinforced 1/4" instrument connection. Available with or without pressure or vacuum gauges. Standard instrument has 2 1/2" gauge face with stainless

steel case. Options include center back mount, acrylic shield for harsh environments, snubber, liquid filled face.

PVC, CPVC, GPP, PP, PVDF



Series GGMU

Ultrapure, zero deadleg instrument isolator with spigot connections. Available with or without pressure gauge. Standard instrument has 2 1/2" gauge face

with stainless steel case. Options include DI water fill and high purity clean/double bag procedure.
PVC, PP, PVDF



Series GGSLE

Isolated pressure or vacuum transducer based on Series GGS. PVC, CP, PP, PF



Series PT

Combination 0-160 PSI pressure and 0-180°F temperature "Tridicator" gauge. Brass connection with 2 1/2" gauge face or stainless steel connection with 3" gauge face.



Series SWT

PTFE diaphragm pressure switch features no wetted metals or elastomers. 16, 25, or 3 Amp models.
PVC, CPVC, PP, PVDF



Series DPG/DPGS

Differential pressure gauge with or without switch. 1/4" connection with 2 1/2" easy-to-read gauge face; 0-15 or 0-30 PSID.
PVC, CPVC



Series DPI/DPIS

Differential pressure indicator with or without switch. 1/8" connection with 1" green/red indicator gauge; 0-15 or 0-30 PSID.
PVC, CPVC



Series FIG/FIGS

Variable area flow indicator with or without switch. 1/4" or 1/2" connection with high visibility gauge; 0-1, 0-2, 0-5, 0-10 PSID.
PVC, CPVC



Series DPFM

Differential pressure flow meter provides clear, understandable flow rate with smaller footprint than typical flow meters. 1/2" or 2" sizes with variety of GPM ranges.
PVC, CPVC



Series CC

Calibration columns feature 100% UV-resistant PVC; remain clear and easy-to-read for years. Rapid fill rates and longer testing periods improve efficiency and accuracy.
100, 250, 500, 1000, 2000 and 4000 ML

SIGHT GLASSES & LEVEL INDICATORS



Series GX

Single-wall sight glass for liquids compatible with acrylic. Fluttering streamers optional.
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3"
PVC, PP



Series GY

Double-wall sight glass for liquids compatible with Pyrex inner wall. Fluttering streamers optional.
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3"
PVC, PP



Series GYW

Double-wall sight glass for liquids compatible with Pyrex inner wall. Flange connections; fluttering device optional.
1 1/2", 2", 3", 4", 6", 8"
PVC, CPVC, PP, PVDF, PTFE



Series GL

Double-wall level indicator for liquids compatible with Pyrex inner wall. 1', 2', 3' or 4' lengths.
1/2", 3/4"
PVC, PP, PTFE

AIR OPERATED DUMP VALVE



Series IDA

Extra high capacity dump valve with spring-return or air x air operation. Drains faster than any competitive quick dump.
4", 5", 6"
PVC, PP, PVDF

AIR OPERATED METERING PUMP



Series VPA

Metering pumps are air-operated, self-priming, positive displacement type pumps designed to meter precise quantities of liquids for dosing or filling, accurate to 1/2 of 1%. The

four sizes of pumps available have a single stroke maximum delivery capacity of 7, 10, 32 or 128 liquid ounces, adjustable to deliver smaller portions.
PVC, PP, PVDF

MANUAL BALL VALVES



Series MBV

The engineered ball valve features trunnion ball design, dual shaft seals, large diameter shaft, mounting lugs, PTFE seats, and perfectly spherical ball. Will

outlive any competitive ball valve. NPT, socket, BSP or metric socket.
3/8", 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4"
or 20 - 110 mm
PVC, CPVC, PP, PVDF



Series TMBV

Three-way version of Series MBV with same trunnion design and features. 2-hole or 3-hole option.
1/2", 3/4", 1", 1 1/2", 2", 3", 4"
PVC, CPVC



Series LMBV

Lateral reducing ball valve based on Series MBV; simplifies and strengthens lateral drops. Includes tee.
1/2", 3/4", 1", 1 1/2", 2" valve
3/4", 1", 1 1/2", 2", 3" tee
PVC, CPVC, PP, PVDF

MANUAL BALL VALVE OPTIONS



Series MBVL
Lock out/tag out option. Available factory complete or as kit for retrofit.
All sizes/materials for Series MBV.



Series MBVM
Metering indicator shows degrees open. For use with regular or characterized ball valve, factory complete or as kit for retrofit. Series MBV sizes to 2" in all materials.



Series MBVSE
Stem extension from 2" to 12". Factory complete or as kit for retrofit.
Series MBV sizes to 2" in all materials.

ACTUATED BALL VALVES



Series ABVA/ABVS
Air x air or fail-safe air x spring actuator for Series MBV, 3/8" 1" sizes. Thermoplastic construction, includes direct manual override. Options include limit stop and limit switch.



Series ABRA/ABRS
Air x air or fail-safe air x spring actuator for Series MBV, 1 1/4" to 4" sizes. Thermoplastic construction, most models include direct manual override
3" & 4" designs features stainless actuator. Options include limit stop and limit switch.



Series EPP
Electro-Pneumatic Positioner turns any air actuated True Blue valve into an electronic control valve. Requires ABRA/ABRS actuator for all sizes.



Series TABVA/TABRA/S
3-way air actuated valves, air x air or fail-safe air x spring versions for Series TMBV.



Series EBVB & EBVF
Premium multi-voltage electric actuators with manual override. Rugged water and dust tight actuator features superior thermoplastic construction built to our specifications. Options include battery backup fail-safe, 4-20 mA or 0-10 VDC electronic control.



Series EBVC
Standard on/off actuator features the same rugged construction as Series EBVB/F. No-frills actuator with superior performance and longevity at a lower cost.



Series TEBVB/TEBVF & TEBVC
3-way electrically actuated valves with the same features as the two-way versions above


MANUAL & ACTUATED BALL VALVE OPTIONS



Flange Connections
Available for most sizes and materials, 2-way and 3-way.



Sanitary Connections
Available for 2-way valves, 1/2" through 2" in PP, PVDF.



Z-Vent Balls
Designed for sodium hypochlorite and other applications prone to dangerous outgassing. Vent allows trapped liquid and resulting gas to escape harmlessly downstream.



ZC Control Balls
Specific angles or special linear cut enables precise control of flow rates for manual valves, or for actuated valves with electronic positioning. All 2-way sizes and materials.

OPTIONS & ACCESSORIES

- High Purity Cleaning Procedure
- Factory setting on pressure control valves
- High Purity Flare Fittings
- Flange Connections
- High Purity Spigots
- Coated Fasteners
- Fail-Dry Sensor

BASIS PRODUCT LINE



Value line of commodity products, manufactured to Plast-O-Matic specifications, with complete technical support. One year warranty. Most products offered with NPT, socket, metric socket, BSP or JIS.

PVC & CPVC standard; most items also available in PP, GPP & PVDF.

- Manual & Actuated Butterfly Valves and Ball Valves
- Ball Checks
- Weir Style Diaphragm Valves
- PTFE Diaphragm Backpressure Valves
- Wye Strainers
- Mini Gauge Guards
- Flow & Level Switches
- Solenoid Valves